POLLUTION CONTROL EQUIPMENTS

In Fiber Handling Section of Asbestos Cement Sheet and Pressure Pipe Plants



POLLUTION CONTROL EQUIPMENTS

In Fiber Handling Section of Asbestos Cement Sheet and Pressure Pipe Plants

Operation of automatic bag opening device:

The function of the equipment is to open the raw asbestos fiber bags automatically in a totally enclosed container without leaving any dust outside.


Removal of the empty bags, discharge of the press packed asbestos fibers in to the lump breaker and breaking the lumps in to fibers.

It also shreds the empty fiber bags into fine particles which are ultimately conveyed along with the fiber.

When equipment is used properly, with all automatic functions, the chances of emission of dust to open atmosphere are practically nil.



LAYOUT OF BAG OPENING DEVICE



- 1). Dust Proof Cover.
- 2). Lifting platform.
- 3). Cutter No 1.
- 4). Cutter No 2.
- 5). Lump Breaker.
- 6). Bag Shredder.
- 7). Blower.
- 8). Rotary Air-Lock.



Operating Pendent



Control Panel



PLASTIC MACHINERY

Visu Casement Compound, Next to Roses Nursery, Chhani Road,
Vadodara - 390002, Gujarat - (India)
Tel: - 0091 - 265 - 2771621 / 2771938 • Fax: - 0091 - 265 - 2330938.
marketing@plasticmachineries.com • gnkurse@sify.com
www.plasticmachineries.com